



1D or 2D
Barcode over 15 m
scan distance

IS-TH1



&



Flexible combination of scan trigger handle and multifunctional smartphone for reliable data recording.

The mobile multifunctional set combines a wide range of functions and possible uses of several devices in one. The **IS-TH1** enables the quick and easy scanning of any 1D or 2D barcodes at close range or at distances of more than 15 meters.

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.



i.safe MOBILE

IS-TH1



ATEX applied for: EX-Zone 1/21
EX-Zone 2/22



IECEx applied for: EX-Zone 1/21
EX-Zone 2/22

RG for „rugged“ environment

TECHNICAL SPECIFICATION

Weight	500 g (without IS530)
Size	200 x 125 x 82 mm
Indication function	Loudspeaker Vibration LED-Display
Power supply	Over IS530 this can be loaded in the handle
Communication	Over the multi functional ISM interface of the IS530

SCAN TYPES

- **IS-TH1MR** (mid range) with **Zebra SE4750 MR** | up to 6 m
- **IS-TH1ER** (extended range) with **Zebra SE4850 ER** | over 15 m



IS530.1



Android™ 9



4,5" Gorilla Glass®
3. generation,
resolution 854 x 480 pixel



3600 mAh battery,
replaceable,
3,8V; 13,68Wh



Bluetooth® 5



GSM 850/900/1800/
1900 MHz
WCDMA: UMTS B1/2/4/5/8
LTE-TDD: B38/B39/B40/B41
LTE-FDD: B1/2/3/4/5/7/8/12
with MFBI B13/14/17/20/25/
26/28A/28B/29/30/66
TD-SCDMA: B34/B39



Qualcomm Snapdragon
SDM660 Octa-Core
Kryo Gold-Quad cores
2.2GHz
Kryo Silver-Quad cores
1.8GHz
4 GB RAM
64 GB internal memory
54 GB accessible



2,4GHz + 5GHz: IEEE
802.11a/ b/g/n/ac/e/k/r/h
mit Hotspot für max. 8
Verbindungen

The complete description you will find on our homepage: www.isafe-mobile.com

➤ i.safe MOBILE and i.safe MOBILE logo are registered trademarks of i.safe MOBILE GmbH. All other trademarks and copyrights are the properties of their respective owners. © 2020 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1040MD01REV03_EN_10.2020